

# Industrial Grade Ethernet Switch 5-port 10/100Mbps Ethernet Switch

Model: NF505F



#### **Overview**

NuFiber's NF505F Industrial Ethernet witch,With 5 Port 10/100 Ethernet ports ,for connecting with devices like computer, switch, hub, server, etc, as well as powering network camera, industrial VoIP phone, wireless AP and other devices. Specially designed for harsh outdoor applications. Its 3KV network port surge protection can adapt to harsh outdoor environment and ensure the reliability of the uninterrupted PoE system. Power input also chooses industry-standard types of power.

### **Features**

- 5 Port 10/100Mbps Ethernet RJ45
- Automatic MAC address learning and aging
- Automatically support IGMP (Multicasting)
- 10/100Mbps Auto-negotiation , auto-MDI-MDI-X
- LED indicators for monitoring power/link/activity

## Shenzhen Nufiber Systems Technology Co., Ltd.



- Supports 10/100Mbps-Full/Half-duplex
- Supports Wall-mount and DIN-Rail installation for lightning protection
- Supports Daisy-Chain connection
- Supports Broadcast Storm Control
- Supports Relay output for power failure
- Super lightening protection, IP40 protection.
- Excellent heat elimination without cooling fan.
- Redundant dual DC power inputs.
- Redundant Power Inputs
- Apply to Urban Intelligent Traffic Monitoring System (ITS), Safe City.
- Harsh industrial environment or higher requirement
- -40  $^{\circ}$ C -85  $^{\circ}$ C operating temperature range.
- 5-Year Warranty

# **Technical Specification**

| Product Name              | 5 Port 10/100Base Industrial Ethernet Switch                      |
|---------------------------|---|
| Product Model             | NF505F  |
| Interface                 | 5x10/100Base-T Ethernet port                                      |
| Network Protocols         | IEEE802.3 10BASE-T; IEEE802.3i 10Base-T;IEEE802.3u;100Base-TX/FX; |
|                           | IEEE802.3ab 1000Base-T; IEEE802.3z 1000Base-X; IEEE802.3x;        |
| Notwork Madia             | 10BASE-T: Cat3,4,5 UTP(≤100 meter)                                |
| letwork Media             | 100BASE-TX: Cat5 or later UTP(≤100 meter)                         |
|                           | Bandwidth: 1Gbps  |
| Performance Specification | Packet Buffer Memory:512 Kbit                                     |
| Specification             | Packet Forwarding Rate:1488000pps/port                            |



Shenzhen Nufiber Systems Technology Co., Ltd.
4/F, Building C, Weihao Industry Park, No.1026, Songbai Road, Xili Town,
Nanshan District, Shenzhen, China Email:candy@nufiber-systems.com

|                 | MAC Address Table: 1K                    |
|-----------------|--|
| Forwarding Mode | Store-and-Forward                        |
| Protection      | Lightening protection, IP40 protection   |
| LED Indicators  | Power: PWR; Link; Link/Act               |
| Power Supply    | Input Power: 2x10~58VDC (Terminal Block) |

# **Other Specifications**

| Working           | Working temperature: -40 $\sim$ 85 $^{\circ}$ C ; Storage temperature: -45 $\sim$ 85 $^{\circ}$ C |
|-------------------|---|
| Environment       | Relative Humidity: 5%~95 %( no condensation)  |
| Industry Standard | FCC CFR47 Part 15,EN55022/CISPR22, Class A EMS:   |
|                   | IEC61000-4-2 (ESD): ±8kV (contact), ±15kV (air)   |
|                   | IEC61000-4-3 (RS): 10V/m (80MHz-2GHz)   |
|                   | IEC61000-4-4 (EFT): Power Port: ±4kV; Data Port: ±2kV   |
|                   | IEC61000-4-5 (Surge): Power Port: ±2kV/DM, ±4kV/CM; Data Port:                                    |
|                   | ±2kV  |
|                   | IEC61000-4-6 (CS): 3V (10kHz-150kHz); 10V (150kHz-80MHz)  |
|                   | IEC61000-4-16 (Common mode conduction): 30V (cont.), 300V (1s)                                    |
| Shell             | IP40 protect grade, metal shell   |
| Installation      | DIN-Rail or Wall mounts   |
| Packing List      | 1×Industrial Ethernet Switch (plus terminal block)  |
|                   | 1×User Manual/Certificate of quality/Warranty card  |
|                   | 1×DIN-Rail mounting kit   |
| Certification     | CE mark, commercial; FCC Part 15 Class B; VCCI Class B  |
|                   | EN 55022 (CISPR 22), Class B  |
| MTBF              | 300,000 hours   |
|                   |   |



#### Shenzhen Nufiber Systems Technology Co., Ltd.

| Wei |               | Product Weight: 0.6KG                      |
|-----|---------------|--|
|     | Maight Q Cina | Packing Weight: 1.1 KG                     |
|     | Weight & Size | Product size (L×W×H): 118mm× 86mm× 34mm    |
|     |               | Packing size(L×W×H): 183mm x 131mm x 100mm |
|     | Warranty      | 5-years                                    |

## **Typical Application**



# **Ordering information**

| │ NF505F | Industrial 5x10/100Mbps RJ45 ports network switch, DIN Rail type, DC10~52V      |
|----------|---|
| │ NF505G | Industrial 5x10/100/1000Mbps RJ45 ports network switch, DIN Rail type, DC10~52V |
| │ NF508F | Industrial 8x10/100Mbps RJ45 ports network switch, DIN Rail type, DC10~52V      |
| │ NF508G | Industrial 8x10/100/1000Mbps RJ45 ports network switch, DIN Rail type, DC10~52V |

NuFiber reserves the right to make changes to the products or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such products or information.

Published by Shenzhen NuFiber Systems Technology Co., Ltd. Copyright © NuFiber

All Rights Reserved



Shenzhen Nufiber Systems Technology Co., Ltd.
4/F, Building C, Weihao Industry Park, No.1026, Songbai Road, Xili Town, Nanshan District, Shenzhen, China Email:candy@nufiber-systems.com

URL: <a href="http://www.nufiber-systems.com">http://www.nufiber-systems.com</a> http://www.nufiber.en.alibaba.com

Sales: Hilary

Email: hilary@nufiber-systems.com

Skype: nsthilary

Wechat: +86-18270837116